


LPI Series Stainless Steel Low Profile Platforms



Standard Features

- Fitted with 4 IP68 stainless steel shear-beam OIML R60 approved load cells each with 350 Ohm input resistance
- Structure and mechanics in AISI304 stainless steel
- Adjustable, shock-proof jointed feet and level
- 5/15 VDC power supply
- Hermetic junction box, IP67 wiring with screened 5m long 6-pin cable with connectors for connection to the indicator
- Fitted with one on/off ramp

Low profile platforms suitable for weighing trolleys, pallet trucks, etc.; fitted with sideboards and an on/off ramp. Suitable for creating scales and electronic weighing systems for all types of industrial and commercial applications. Standard version is with approved load cell. Available also in the Ex II 2GD IIC ATEX version in stainless steel.

Specifications


Options Only Available at Time of Order:

- Connection to the indicator and calibration with CE-M 3000e single range or 3000e + 3000e dual range approval (depending on the indicators used).
- High resolution model for internal factory use.

Options for ATEX Version:

- CCATEX: ATEX certificate for each load cell
- JB4QA: ATEX certified junction box
- DCATEXMECH: ATEX declaration for the PLATFORM (for the load cells ATEX declaration see CCATEX-1 code). Option to be offered only if the platform is ordered without the indicator, if so, refer to the chosen weight indicator available certifications

Connector Pinout



Pin	Signal	Color
1	EXC+	Red
2	EXC-	Black
3	SENSE-	Blue
4	SENSE+	Yellow
5	SIG-	White
6	SIG+	Green
7	SHIELD	Yellow

Available Versions

Code	l x w x h (mm)	Nr. of cells	Max (g)	d (g)	M (g*)	2R (g)*	d HR (g)*
LPCI3-1	800x800x45	4x300kg	300	50	100	--	20
LPCI6-1	800x800x45	4x500kg	600	100	200	100-200	50
LPEI6-1	1250x1000x45	4x500kg	600	100	200	100-200	50
LPEI15-1	1250x1000x45	4x1000kg	1500	200	500	200-500	100
LPFI6-1	1500x1250x45	4x500kg	600	100	200	100-200	50
LPFI15-1	1500x1250x45	4x1000kg	1500	200	500	200-500	100

(*) Divisions obtainable only with the relative options, in combination with Dini Argeo weight indicator.

Parts

Part #	Description
{#Available Versions}	
LPCI3-1	Stainless steel low profile platform Max=300kg, d=50g, 800x800x45mm, for weighing carts and pallet truck, 1 on/off ramp, stainless steel loading surface and structure. 5 m shielded cable.
LPCI6-1	Stainless steel low profile platform Max=600kg, d=100g, 800x800x45mm, for weighing carts and pallet truck, 1 on/off ramp, stainless steel loading surface and structure. 5 m shielded cable.
LPEI6-1	Stainless steel low profile platform Max=600kg, d=100g, 1000x1250mm h=45mm, for weighing carts and pallet truck, 1 on/off ramp, stainless steel loading surface and structure. 5 m shielded cable.
LPEI15-1	Stainless steel low profile platform Max=1500kg, d=200g, 1000x1250mm h=45mm, for weighing carts and pallet truck, 1 on/off ramp, stainless steel loading surface and structure. 5 m shielded cable.
LPFI6-1	Stainless steel low profile platform Max=600kg, d=100g, 1250x1500mm h=45mm, for weighing carts and pallet truck, 1 on/off ramp, stainless steel loading surface and structure. 5 m shielded cable.
LPFI15-1	Stainless steel low profile platform Max=1500kg, d=200g, 1250x1500mm h=45mm, for weighing carts and pallet truck, 1 on/off ramp, stainless steel loading surface and structure. 5 m shielded cable.

Options

Part #	Description
{#Calibration service with weight indicator}	
DINICAL	Connection to a Dini Argeo indicator and calibration. NET PRICE (*).
DINICAL-DRC	Direct connection (without connectors) from platform to indicator and calibration service. € NET.NOTE(1): delivered platform not connected: connection of the platform to the weight indicator to be carried out on site by qualified personnel.
{#Legal for trade approval, class III or IIIB, with Dini Argeo weight indicator (only at time of order)}	
ECEM	3000e legal for trade approval, for single platform/scale. NOTE: Depending on the product, the ECEM approval service may require DINICAL calibration service. Check to see if DINICAL is in the product options.
ECEM2	Multi-range 3000+3000e legal for trade approval, for single platform/scale. NOTE: Depending on the product, the ECEM approval service may require DINICAL calibration service. Check to see if DINICAL is in the product options.
ECEMDOC	Printed EU declaration of conformity, EU certificate of verification, test certificate and metrological book (free download from our website, only for approved CE-M products). NET €.
{#High resolution (d HR) (only at time of order)}	
ETHR	High resolution model for internal factory use.
{#IP68 protection}	
ETIP68	IP68 connection fitted with specific cable, fairleads and connectors.
{#Additional On / Off ramp}	
LPCRI-1	Second stainless steel ramp for LPC platforms, 800x800mm.
LPERI-1	Second stainless steel ramp for LPE platforms, 1000x600mm.
LPFRI-1	Second stainless steel ramp for LPF platforms, 1250x600mm.
LPCISTP	Stainless steel end rails for LPCI platform.
{#Floor columns}	
CSP38I-1	AISI 304 stainless steel column 450x450mm, h=917mm, Ø 38mm. For the indicators of the DINI ARGEO and SCALE HOUSE range.
CSP38	Stainless steel column 450x450mm, h=917, Ø 38mm. Painted steel base. For the indicators of the DINI ARGEO and SCALE HOUSE range.
CSP38D	Stainless steel column 350x350mm, h=750mm. Painted steel base. For the indicators of the DINI ARGEO and SCALE HOUSE range.
{#Plates for fixing on the floor}	
ETPFI-1	Kit of 4 plates for fixing on the floor, in stainless steel. For platforms ETG, ETH, ETL, ETA, ETM, ETB, ETD, ETE, ETF, LPI and FL series.
{#Options for ATEX version}	
CCATEX-1	Optional ATEX version for single load cell. Marking: ATEX II 1G Ex ia IIC T6 (Ta -20÷+40°C) TX (Ta -20÷+65°C) Ga and ATEX II 1D Ex ta IIIC TX°C (Ta -20÷+40°C) TX°C (Ta -20÷+65°C) Da IP65. Provided with safety instructions and the ATEX EU declaration of conformity (EN, DE, FR, ES and IT).
CCATEX3GD	ATEX certificate for each load cell. Marking: ATEX II 3G Ex nA IIC T6 Gc for gas and ATEX II 3D Ex tc IIIC T115°C Dc IP65 for dusts. Complete with manual and ATEX CE conformity declaration (available in EN, DE, FR and IT).
JB4QAP	Equalisation box for stainless steel pallet-weighing scales for hazardous areas. Protection modes: ATEX II 2G Ex ib IIC T6 Gb for gases, ATEX II 2D Ex tb IIIC T115°C Db IP65 for dusts. Complete with manual and ATEX CE CONFORMITY DECLARATIONS (available in EN, DE, FR and IT). (Only suitable with stainless steel version)
DCATEXMECH	ATEX version for the PLATFORM / LOAD CELL MOUNTING KIT for zone 1/21 (for the load cells ATEX declaration see CCATEX code). Option to be offered only if the platform is ordered without the indicator, otherwise refer to the available certifications for the chosen weight indicator. Provided with safety instructions and ATEX EU declaration of conformity (EN, DE, FR, ES and IT).
{#Protection for junction box / electronic circuits}	
GELBOX	Anti condensation, insulating, and sealing gel. Useful to protect the electronic circuits of the weighing system, even under prolonged immersions conditions. Pack of 300ml.
{#Calibration service with Dini Argeo weight indicator (only at time of order)}	

Part #	Description
CT6	ISO 17025 calibration certificate from 301 to 1500 kg for single scale/platform. For precision and industrial scales, crane scales. The certificate is provided in digital format (pdf) and sent by e-mail.

Dini Argeo S.r.l. | Via della Fisica, 20 - 41042, Spezzano di Fiorano, Modena (MO), Italy | Tel.: +39 0536 843418

www.diniargeo.com
