

WALL-E INOX Series Stainless Steel Bench and Floor Scales



Standard Features

- Weight indicator with waterproof IP65 stainless steel case. Backlit 25mm LCD display with 6 high contrast digits and icons for indication of active functions. Waterproof 5-key functional keypad.
- Functions with an aluminium load cell, protected in IP65 stainless steel cover, approved according to OIML R60 C3 standards (3000 divisions).
- Stainless steel structure, with adjustable resting feet and level.
- Stainless steel loading surface, size: see the table.
- Support column, height:
 - 350 mm in the "T" models;
 - 500 mm in the "Q" models;
 - 700 mm in the "X" models.
- Length of connection cable to the indicator: 3m.
- Digital calibration and set-up from keypad or from PC with DINITOOLS.
- Power supply: 110 - 240 VAC power supplier.

Bench and floor scales with column, characterized by multifunction weight indicator, completely stainless steel structure. Easy to use and versatile, guaranteeing precision and reliability. Particularly suitable for industrial and commercial use. Available also in CE-M approved version according to OIML R-76 / EN 45501 standards.

WALL-E INOX Series Specifications

I/O Section:

- RS232/C port configurable for connection with printer/labeller, or for attached printer.
- RS232/C (or optionally RS485) bi-directional port configurable for PC, PLC, remote display, and radio modem. Quick RJ RS232 plug connection.

Keyboard Functions:

Zeroing, Automatic tare, Preset tare, printing and/or data transmission, selectable function command, on/off switching, backlit setting, function mode quick selection, user menu.

Options When Ordering:

- CE-M 3000e approved (OIML R-76 / EN 45501).

Selectable Function Modes:

- High resolution display x 10
- Precision weighing with temporary recalibration via a sample weight (*for internal factory use*)
- Net/Gross
- Newton to Kg converter
- Lb to Kg converter
- Free conversion factor (for meter and litre counters etc.)
- Weight totalizer
- Formulizer
- +/- controller with quick target and threshold input
- Percentage weighing
- Percentage batching with programmable target
- Piece counter
- Hold

Optional functions:

- PEAK, detection of weight peaks (code DFWPK)
- Newton to Kg converter (code DFWPK)

Accessing User Menu:

Use the dedicated key* to adjust the weighing filter, date and time, setpoint and tare weight, which the user can access by entering a programmable access password.

** These quick access keys to the menus can be blocked by configuring a dedicated password.*

Available Versions

Code	I x w x h (mm)	Max (kg)	d (g)	M (g*)
<u>WETI6-2</u>	300x300x130	6	2	-
<u>WETI15-2</u>	300x300x130	15	5	5
<u>WETI30-2</u>	300x300x130	30	10	10
<u>WEQI30-2</u>	400x400x140	30	10	10
<u>WEQI60-2</u>	400x400x140	60	20	20
<u>WEQI150-2</u>	400x400x140	150	50	50
<u>WEXI60-2</u>	600x600x165	60	20	20
<u>WEXI150-2</u>	600x600x165	150	50	50
<u>WEXI300-2</u>	600x600x165	300	100	100

(*) These divisions are obtainable only with the relative options.

Parts

Part #	Description
{#Available versions}	
WETI6-2	Bench and floor scale with 6 kg capacity, 2 g division, stainless steel structure and loading surface, 300x300 mm size, backlit LCD display, membrane waterproof keyboard and indicator support column, 350 mm height.
WETI15-2	Bench and floor scale with 15 kg capacity, 5 g division, stainless steel structure and loading surface, 300x300 mm size, backlit LCD display, membrane waterproof keyboard and indicator support column, 350 mm height.
WETI30-2	Bench and floor scale with 30 kg capacity, 10 g division, stainless steel structure and loading surface, 300x300 mm size, backlit LCD display, membrane waterproof keyboard and indicator support column, 130 mm height.
WEQI30-2	Bench and floor scale with 30 kg capacity, 10 g division, stainless steel structure and loading surface, 400x400 mm size, backlit LCD display, membrane waterproof keyboard and indicator support column, 500 mm height.
WEQI60-2	Bench and floor scale with 60 kg capacity, 20 g division, stainless steel structure and loading surface, 400x400 mm size, backlit LCD display, membrane waterproof keyboard and indicator support column, 500 mm height.
WEQI150-2	Bench and floor scale with 150 kg capacity, 50 g division, stainless steel structure and loading surface, 400x400 mm size, backlit LCD display, membrane waterproof keyboard and indicator support column, 500 mm height.
WEXI60-2	Bench and floor scale with 60 kg capacity, 20 g division, stainless steel structure and loading surface, 600x600 mm size, backlit LCD display, membrane waterproof keyboard and indicator support column, 700 mm height.
WEXI150-2	Bench and floor scale with 150 kg capacity, 50 g division, stainless steel structure and loading surface, 600x600 mm size, backlit LCD display, membrane waterproof keyboard and indicator support column, 700 mm height.
WEXI300-2	Bench and floor scale with 300 kg capacity, 100 g division, stainless steel structure and loading surface, 600x600 mm size, backlit LCD display, membrane waterproof keyboard and indicator support column, 700 mm height.

Options

Part #	Description
{#International power cables}	
PWCORDAUS	Version with AU power cord.
PWCORDUK	Version with BS1363 power cord (UK plug).
PWCORDCH	Power supply cord with SEV1011 plug (CH plug).
PWCORDUS	Version with US type B power cord (Japan, North and Central America).
{#Calibration service (ACCREDIA/DAKKS) only at time of order}	
CT4	ISO 17025 calibration certificate from 6 to 60 kg for single scale/platform. For precision and industrial scales, crane scales. The certificate is provided in digital format (pdf) and sent by e-mail.
CT5	ISO 17025 calibration certificate from 61 to 300 kg for single scale/platform. For precision and industrial scales, crane scales. The certificate is provided in digital format (pdf) and sent by e-mail.
{#Legal for Trade Approval (only at time of order)}	
ECCEM	3000e legal for trade approval, for single platform/scale. NOTE: Depending on the product, the ECEM approval service may require DINICAL calibration service. Check to see if DINICAL is in the product options.
ECENDOCC	Printed EU declaration of conformity, EU certificate of verification, test certificate and metrological book (free download from our website, only for approved CE-M products). NET €.
{#Storing weighments}	
SWM	"WeiMonitor" PC program to monitor and record in real time weighs performed on the connected scale (the price is intended for the license to manage one scale).
{#Connection cables}	
RSCBUSB-1	USB PC/RS232 converter cable, l=1,5m. USB/RJ11 connector.
{#Columns, supports brackets, visors}	
PBISTF	Stainless steel fixing bracket for mounting the DFwLI indicator.

Dini Argeo S.r.l. | Via della Fisica, 20 - 41042, Spezzano di Fiorano, Modena (MO), Italy | Tel.: +39 0536 843418

www.diniargeo.com